



SZ 100-11

Sleeve Type Air Actuator



Purchase order data

Type	Order No.
with plastic connecting parts, G3/8 air inlet	on request

Additional types on request

Technical data

Min. pressure	0.9 bar
Return force to min height	≤ 900 N
Overall weight	0.7 kg

Vibration isolation - dynamic characteristic values

Design height H: recommended 150mm, guidance in lateral direction required

Pressure p [bar]	3	4	5	6	7	8	Vol. V [l]
Force (Load) [kN]	2.8	3.7	4.7	5.7	6.8	7.8	1.2
Spring rate [N/mm]	43.5	54.5	65.5	76.5	87.5	98.5	
Natural frequency [Hz]	2.0	1.9	1.9	1.8	1.8	1.8	

Pneumatic application - static characteristic values

Force F [kN]

Pressure p	[bar]	3	4	5	6	7	8	Vol. V [l]
Height H [mm]	175	2.7	3.6	4.55	5.45	6.4	7.3	1.5
	160	2.75	3.7	4.7	5.7	6.7	7.7	1.3
	145	2.75	3.7	4.75	5.8	6.8	7.8	1.1
	130	2.75	3.75	4.8	5.8	6.8	7.8	1
	115	2.8	3.8	4.8	5.8	6.8	7.8	0.85
	100	2.8	3.8	4.8	5.8	6.8	7.8	0.69



Service instructions
M30x1.5: max. 40 Nm
M8: max. 5 Nm
G3/8: max. 10 Nm

Measuring procedure: Room temperature / Force-height-data quasistatic / Dynamic data at 1 Hz